



## **SR150** Wireless Siren with Built-in Strobe

**M**  **GELLAN**  **N**<sup>™</sup>

### **KEY FEATURES:**

- Compatible with MG Series V4.0 and SP series V4.0 when using an RTX3 V1.5.
- Built-in transceiver (433MHz or 868MHz).
- 100db wireless siren with integrated strobe light.
- Weather-resistant design using a PC/ABS enclosure with UV protection and a silicone coated PCB (-20°C to 50°C / -4°F to 122°F).
- Battery powered only, no need for AC power.
- Fast alarm response time (4 seconds).
- 2.5 hour alarm display (strobe flashes every 4 seconds after bell cut-off).
- Siren presence supervised by control panel.
- Panel presence supervised by siren (activates siren and strobe for 5 minutes if communication is lost squawk once and flash every 4 seconds).
- Triple tamper protection (screw removal, cover removal, and removal from wall).
- Assign up to 4 sirens per control panel.
- In-field firmware upgradeable via 307USB.
- Siren test mode.
- 4-LED signal strength and status display.
- Strobe lens available in blue.
- Fully powered using three 1.5Vdc type "D" alkaline batteries (included). Not required, but can also be powered using 8-16Vac / 9-20Vdc power supply.
- Dimensions: 24cm x 6cm x 18cm (9.5in x 2.3in x 7 in).